
STATE OF ILLINOIS DEPARTMENT OF TRANSPORTATION

SHEET NO. 1270 TOTAL SHEET NO. F.A.U. 9105 (IL.) 119 BR MADISON 425 179C 281 SHEETS F.A.U. 5408 (MO.)


> Symm, about € Roadway

Contract No. 76561




SECTION B-B THRU PIER 31

(Looking West)



SECTION C-C THRU PIER 32 (Looking East)




The exterior surfaces of the furnished Fiberglass Pipe shall be coated or pigmented by the manufacturer with a color that matches the color of concrete. Fiberglass Pipe shall conform to ASTM D2996, with short-time rupture strength

hoop tensile stress of 30,000 psi minimum. The surface of the Fiberglass Pipe shall be free of bond inhibiting agents.


The Clamping Device and inserts shall be galvanized according to AASHTO 232. Space Pipe Clamp in new construction to miss reinforcement.

The cost of Pipe, Reducers, Clamps, attachment hardware, Fabric Pad, Concrete Headwall and Installation is included with "Drainage System".



PIPE CLAMP DETAIL AT GIRDER

* Dimension as required by Pipe Clamp.



PIPE CLAMP DETAIL FOR PIER

l₈" Fabric

** Dimension as required by Pipe Clamp.

6′′ ø

Pipe Clamp

Galvanized Steel Rods

Threaded Coil

Loop Inserts.

Reinforcement Bars

threaded both ends

Pipe connected to girder

Pier 32 Сар

 $2^{3}4''$ (min,)

Pipe connected to Pier 32

> DRAINAGE SYSTEM DETAILS F.A.U. RT. 9105 (IL.) F.A.U. RT. 5408 (MO.) SEC. 119BR MADISON COUNTY STATION 100+00.00 STRUCTURE NO. 060-6002

SECTION A-A

SEM DESIGNED CHECKED DRAWN BECKY M. CURRY SEM & CCC



